



- Notes:
1. 4.3" Transmissive, Normally-White TFT-LCD Module
  2. View Direction: 6:00
  3. LCD Drivers: OTA5180A
  4. Interface: 24-Bit Parallel RGB
  5. Backlight: 10 LEDs
  6. Touch Panel: 4-Wire Analog
  7. Operation Temp.:  $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$
  8. Storage Temp.:  $-30^{\circ}\text{C} \sim 80^{\circ}\text{C}$

PIN NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
SYMBOL	K	A	GND	VDD	R0	R1	R2	R3	R4	R5	R6	R7	G0	G1	G2	G3	G4	G5	G6	G7
PIN NO.	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
SYMBOL	B0	B1	B2	B3	B4	B5	B6	B7	GND	DCLK	DISP	HSYNC	VS	DE	NC	GND	X1	Y1	X2	Y2

DWN.	YDY	TITLE	LCM OUTLINE DIMENSION	
CHK.	LY	PART NO.	LTO43A-O2AT	
APPD.		DWG. NO.	LTO43A-O2AT-WXA	
REV.	A	UNIT	mm	PROJECTION
DATE	'09.02.12	SCALE	NTS	SHEET 1 OF 1